



Pipe Fittings & Fabrications for Industrial Service

P.O. Box 1220, Nash, TX 75569-1220
 Phone: 903-832-2581, Fax 903-838-6260
 www.jcmindustrialfittings.com

Contact JCM: Call Toll Free 800-527-8482
 Fax Toll Free 800-874-9524
 sales@jcmindustrialfittings.com

JCM Fabricated Reducing Steel Flanged Coupling Adapters for Industrial Service

JCM 304 Fabricated Reducing Flanged Coupling Adapters

The JCM 304 Fabricated Reducing Flanged Coupling Adapter provides a simple means of joining plain end pipe to smaller or larger nominal sized flanged fittings, valves and equipment. Ideal for installing flanged valves, backflow preventors, monitoring equipment and other pipeline accessories to be retrofitted into a piping system. Fabricated without pipe stops, the JCM 303 Flanged Adapter can be slid back on the plain end pipe for quick fitting installation and adjustment. Available as an increaser or reducer.



For specific application submittal, please provide the following information:

- Type of pipe
- Size/Outside Diameter of Pipe
- Flange size and type (see below)
- Line Content and Temperature
- Working and Test Pressure Requirements
- Installation environmental concerns, spacial or limited access information

NOMINAL PIPE SIZE		PIPE O.D. RANGE		CATALOG NUMBER	(X) ADD FLANGE SIZE
IN	MM	IN	MM		
4	100	4.50	114	304-0450	X
4	100	4.80 - 5.00	121 - 127	304-0480	X
5	125	5.56	141	304-0556	X
6	150	6.63	168	304-0663	X
6	150	6.90 - 7.10	175 - 180	304-0690	X
8	200	8.63	219	304-0863	X
8	200	9.05 - 9.30	229 - 236	304-0905	X
10	250	10.75	273	304-1075	X
10	250	11.10 - 11.40	281 - 289	304-1110	X
12	300	12.75	323	304-1275	X
12	300	13.20 - 13.50	335 - 342	304-1320	X
14	350	14.00	355	304-1400	X
14	350	15.30	388	304-1530	X
14	350	15.65	397	304-1565	X
16	400	16.00	406	304-1600	X
16	400	17.40	441	304-1740	X
16	400	17.80	452	304-1780	X
18	450	18.00	457	304-1800	X
18	450	19.50	495	304-1950	X
18	450	19.92	505	304-1992	X
20	500	20.00	508	304-2000	X
20	500	21.60	548	304-2160	X
20	500	22.06	560	304-2206	X
24	600	24.00	609	304-2400	X
24	600	25.80	655	304-2580	X
24	600	26.32	668	304-2632	X

STANDARD AVAILABLE FLANGE SIZES
2
3
4
6
8
10
12
14
16
18
20
24

OTHER SIZES AVAILABLE UPON REQUEST.

**Typical Application:
Connection
Temporary/Permanent
Connection/Insertion
REDUCING**

**Valves
Backflow Preventors
Flanged Fittings
Monitoring Equipment
Flow meters**

**For application parameters,
contact JCM Engineered and
Technical Sales
800-527-8482 or 903-832-2581**